

United States Patent and Trademark Office

UNITED STATES DEPARTMENT OF COMMERCE United States Patent and Trademark Office Address: COMMISSIONER FOR PATENTS P.O. Box 1450 Alexandria, Virginia 22313-1450 www.uspto.gov

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
10/017,585	12/18/2001	Suk Won Choi	8733.534.00	6155
30827 7	590 10/15/2004		EXAMINER	
MCKENNA LONG & ALDRIDGE LLP			LEWIS, DAVID LEE	
1900 K STREET, NW WASHINGTON, DC 20006			ART UNIT	PAPER NUMBER
			2673	
			DATE MAILED: 10/15/2004	4 6

Please find below and/or attached an Office communication concerning this application or proceeding.

	Application No.	Applicant(s)				
	10/017,585	CHOI ET AL.				
Office Action Summary	Examiner	Art Unit				
	David L Lewis	2673				
The MAILING DATE of this communication appears on the cover sheet with the correspondence address Period for Reply						
A SHORTENED STATUTORY PERIOD FOR ITHE MAILING DATE OF THIS COMMUNICAT - Extensions of time may be available under the provisions of 37 after SIX (6) MONTHS from the mailing date of this communica - If the period for reply specified above is less than thirty (30) day - If NO period for reply is specified above, the maximum statutory - Failure to reply within the set or extended period for reply will, b Any reply received by the Office later than three months after the earned patent term adjustment. See 37 CFR 1.704(b).	CION. CFR 1.136(a). In no event, however, may a stion. s, a reply within the statutory minimum of thir period will apply and will expire SIX (6) MON y statute, cause the application to become AB	reply be timely filed ty (30) days will be considered timely. NTHS from the mailing date of this communication. BANDONED (35 U.S.C. § 133).				
Status						
1) Responsive to communication(s) filed or	1 <u>22 June 2004</u> .					
2a)⊠ This action is FINAL . 2b)□	This action is FINAL. 2b) This action is non-final.					
	Since this application is in condition for allowance except for formal matters, prosecution as to the merits is closed in accordance with the practice under <i>Ex parte Quayle</i> , 1935 C.D. 11, 453 O.G. 213.					
Disposition of Claims						
4) Claim(s) 1-21 is/are pending in the application 4a) Of the above claim(s) is/are with 5) Claim(s) is/are allowed. 6) Claim(s) 1-21 is/are rejected. 7) Claim(s) is/are objected to. 8) Claim(s) are subject to restriction	ithdrawn from consideration.					
Application Papers						
9)☐ The specification is objected to by the Examiner.						
10)☐ The drawing(s) filed on is/are: a)☐ accepted or b)☐ objected to by the Examiner.						
Applicant may not request that any objection to the drawing(s) be held in abeyance. See 37 CFR 1.85(a).						
Replacement drawing sheet(s) including the correction is required if the drawing(s) is objected to. See 37 CFR 1.121(d). 11) The oath or declaration is objected to by the Examiner. Note the attached Office Action or form PTO-152.						
Priority under 35 U.S.C. § 119						
12) Acknowledgment is made of a claim for for a) All b) Some * c) None of: 1. Certified copies of the priority docu 2. Certified copies of the priority docu 3. Copies of the certified copies of the application from the International E * See the attached detailed Office action for	uments have been received. uments have been received in A e priority documents have been Bureau (PCT Rule 17.2(a)).	pplication No received in this National Stage				
Attachment(s)						
1) Notice of References Cited (PTO-892) 4) Interview Summary (PTO-413)						
Notice of Draftsperson's Patent Drawing Review (PTO-948) Paper No(s)/Mail Date Notice of Draftsperson's Patent Drawing Review (PTO-948) Paper No(s)/Mail Date Notice of Informal Patent Application (PTO-152) Other:						

Art Unit: 2673

DETAILED ACTION

Claim Rejections - 35 USC § 102

The following is a quotation of the appropriate paragraphs of 35 U.S.C. 102 that form the basis for the rejections under this section made in this Office action:

A person shall be entitled to a patent unless -

- (e) the invention was described in (1) an application for patent, published under section 122(b), by another filed in the United States before the invention by the applicant for patent or (2) a patent granted on an application for patent by another filed in the United States before the invention by the applicant for patent, except that an international application filed under the treaty defined in section 351(a) shall have the effects for purposes of this subsection of an application filed in the United States only if the international application designated the United States and was published under Article 21(2) of such treaty in the English language.
- 1. Claims 1-21 are rejected under 35 U.S.C. 102(e) as being anticipaed by Mizutani et al. (6392620 B1).
- 2. As in claim 1, Mizutani et al. teaches of a ferroelectric liquid crystal display, figures 1 and 2, column 5 lines 41-67, column 6 lines 1-2, comprising: a liquid crystal panel including liquid crystal and at least one liquid crystal cell arranged at a crossing area at of a gate line and a data line, column 5 lines 41-67, figure 2 items 8, 11, 1b; a data processor supplying red, green and blue data signals to said at least one liquid crystal cell, column 8 lines 1-10, figure 2 item 23; and a backlight in a stand-by state during a responding period of the liquid crystal corresponding to each of said supplied red, green and blue data signals, for generating red, green and blue light at the end of each responding period, figure 3B item F12 or BL, column 8 lines 60-67, wherein the backlight generates the

red, green, and blue light in correspondence with the red, green, and blue data signals, figure 3B item F12 or BL, column 8 lines 60-67, column 10 lines 33-53.

- 3. As in claim 2, Mizutani et al. teaches of, wherein said liquid crystal panel comprises: a upper substrate on which a common electrode and a first alignment film are sequentially disposed, figure 1 item 3a, column 5 lines 60-65; and a lower substrate on which a thin film transistor, a pixel electrode and a second alignment film are sequentially disposed, figure 1 item 3b, column 5 lines 60-65; wherein the liquid crystal is a ferroelectric liquid crystal interposed between said upper substrate and said lower substrate, figure 1 item 2, column 6 line 1. As in claim 3, Mizutani et al. teaches of, wherein said backlight includes a backlight driver for supplying an electrical signal to generate red, green and blue light, figure 2 item 22. As in claim 4, Mizutani et al. teaches of, further comprising a backlight controller for supplying a control signal to generate red, green and blue light, figure 2 item 23. As in claim 5, Mizutani et al. teaches of said ferroelectric liquid crystal responds according to said red, green and blue data signals, column 3 lines 15-43.
- 4. As in claim 6, Mizutani et al. teaches of a method of driving a ferroelectric liquid display, column 6 lines 1-2, comprising: sequentially supplying red, green and blue data signals to a liquid crystal cell of a liquid crystal panel, column 8

Art Unit: 2673

lines 35-45, figure 3A item F1, figure 13 item F11, wherein liquid crystal in the liquid crystal cell responds to each of said supplied red, green and blue data signals during a responding period, figure 13 item LC response, column 10 lines 5-25; and sequentially generating red, green and blue light at the end of each responding period, wherein red, green, and blue light is generated in correspondence with the red, green and blue data signals, figure 13 item illumination/transmitted light quantify, column 8 lines 35-44, column 10 lines 33-53.

5. As in claim 7, Mizutani et al. teaches of wherein a backlight is in a stand-by state during the responding period, figure 3A item BL. As in claim 8, Mizutani et al. teaches of wherein said red, green and blue data signals sequentially are applied to the liquid crystal cell at least once during a frame period, figure 3A item F1 and F2. As in claim 9, Mizutani et al. teaches of wherein the liquid crystal cell includes a ferroelectric liquid crystal, figure 2 item 2, column 6 line 1.

As in claim 10, Mizutani et al. teaches of further comprising: supplying a red data signal to said liquid crystal cell and then irradiating a red light, during a frame period, figure 13 item F11 (R); supplying a green data signal to said liquid crystal cell and then irradiating a green light, during said frame period, figure 13 item F11 (G); and supplying a blue data signal to said liquid crystal cell and then irradiating a blue light, during said frame period, figure 13 item F11 (B). As in claim 11, Mizutani et al. teaches of wherein after each of the red, green and

Art Unit: 2673

blue data signals is supplied, there is a time for the liquid crystal to respond to each respective data signal, figure 13 item LC response. As in claim 12, Mizutani et al. teaches of wherein after at least one of the red light, green light and blue light is irradiated for a predetermined time, figure 3A item R, another data signal for another color is immediately supplied, figure 3A item B.

6. As in claim 13, Mizutani et al. teaches of a liquid crystal display device. comprising: a liquid crystal panel, figures 1 and 2, column 5 lines 35-65, including: a plurality of gate signal lines, figure 2 item 8, column 5 lines 35-65; a plurality of data signal lines, figure 2 item 11, column 5 lines 35-65; liquid crystal cells in a matrix at crossing points of the gate and data signal lines, the liquid crystal cells having a liquid crystal therein, figure 2 item 1b, column 5 lines 35-65; a data driver for supplying data signals to the data signal lines, figure 2 item 13, column 6 lines 3-17; a gate driver for supplying gate signals to the gate signal lines, figure 2 item 12, column 6 lines 3-17; a controller for receiving a plurality of signals from an interface, figure 2 item 23, column 6 lines 50-60; and a backlight in a stand-by state during responding periods as the liquid crystal responds to the data signals after the data signals are supplied to the liquid crystal cells and generating light at the end of each responding period. figure 2 item A, figure 3A item BL, column 8 lines 60-67, column 10 lines 33-**53**.

Page 6

Application/Control Number: 10/017,585

Art Unit: 2673

7. As in claim 14, Mizutani et al. teaches of wherein the data signals include red, green and blue data signals, figure 3A item F1. As in claim 15, Mizutani et al. teaches of, wherein the plurality of signals include a control signal, figure 2 item 23, column 6 lines 50-60. As in claim 16, Mizutani et al. teaches of wherein the plurality of signals include a horizontal synchronization signal, column 6 lines 50-60, wherein said synchronization signal is one of horizontal and vertical as well known. As in claim 17, Mizutani et al. teaches of wherein the plurality of signals include a vertical synchronization signal, column 6 lines 50-60, wherein said synchronization signal is one of horizontal and vertical as well known. As in claim 18, Mizutani et al. teaches of wherein the plurality of signals include an input clock signal, column 7 lines 65-68. As in claim 19, Mizutani et al. teaches of wherein the plurality of signals include a data enable signal, column 7 lines 44-68. As in claim 20, Mizutani et al. teaches of wherein controller is capable of receiving a horizontal synchronization signal and a vertical synchronization signal and generating a gate start clock and a gate scanning pulse to be supplied to the gate driver, figure 2 item 23. As in claim 21. Mizutani et al. teaches of wherein the controller is capable of receiving data signals and generating red, green and blue data signals and a data enable signal to be supplied to the data driver, figure 2 item 23.

Response to Arguments

Art Unit: 2673

8. Applicant's arguments filed 6/22/2004 have been fully considered but they are not persuasive. Mizutani anticipates the claimed invention. Wherein Mizuntani teaches of said processor supplying sequential color signals, figure 2 item 23, and said backlight in a stand by state, figure 3B item BL or F12, wherein the backlight generates the color display in correspondence to the color signals, column 8, and column 10 lines 33-53. Rejection maintained.

Conclusion

9. Applicant's amendment necessitated the new ground(s) of rejection presented in this Office action. Accordingly, THIS ACTION IS MADE FINAL. See MPEP § 706.07(a). Applicant is reminded of the extension of time policy as set forth in 37 CFR 1.136(a). A shortened statutory period for reply to this final action is set to expire THREE MONTHS from the mailing date of this action. In the event a first reply is filed within TWO MONTHS of the mailing date of this final action and the advisory action is not mailed until after the end of the THREE-MONTH shortened statutory period, then the shortened statutory period will expire on the date the advisory action is mailed, and any extension fee pursuant to 37 CFR 1.136(a) will be calculated from the mailing date of the advisory action. In no event, however, will the statutory period for reply expire later than SIX MONTHS from the date of this final action.

Art Unit: 2673

10. Any inquiry concerning this communication or earlier communications from the examiner should be directed to David L Lewis whose telephone number is 703 306-3026. The examiner can normally be reached on M, T, TH, F. If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor, Bipin Shalwala can be reached on 703 305-4938. Any inquiry of a general nature or relating to the status of this application or proceeding should be directed to the receptionist whose telephone number is 703 305-4700.

Any response to this action should be mailed to:

Commissioner of Patents and Trademarks Washington, D.C. 20231

or faxed to:

(703) 872-9314 (for Technology Center 2600 only)

Hand-delivered responses should be brought to Crystal Park II, 2121 Crystal Drive, Arlington, VA, Sixth Floor (Receptionist).

Any inquiry of a general nature or relating to the status of this application or proceeding should be directed to the Technology Center 2600 Customer Service Office whose telephone number is (703) 306-0377.

October 13, 2004

BIPIN SHALWALA SUPERVISORY PATENT EXAMINER TECHNOLOGY CENTER 2600